# **SAFETY DATA SHEET**



#### Marathane

Section 1. Identif	fication
GHS product identifier	: Marathane
Other means of identification	: Not available.
Product type	: Liquid.
Relevant identified uses of Not applicable.	f the substance or mixture and uses advised against
Supplier's details	: Betco Corporation 1001 Brown Avenue Toledo, OH 43607 www.betco.com 888-462-3826
Emergency telephone number (with hours of operation)	: Chemtrec 800-424-9300 (24 Hour)
Section 2. Hazar	ds identification
OSHA/HCS status	: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	<ul> <li>FLAMMABLE LIQUIDS - Category 3 SKIN CORROSION/IRRITATION - Category 2 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3</li> </ul>
GHS label elements	
Hazard pictograms	
Signal word	: Warning
Hazard statements	<ul> <li>Flammable liquid and vapor.</li> <li>Causes serious eye irritation.</li> <li>Causes skin irritation.</li> <li>May cause drowsiness and dizziness.</li> </ul>
Precautionary statements	<u>5</u>
Prevention	: Wear protective gloves. Wear eye or face protection: Recommended: splash goggles. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep container tightly closed. Use only outdoors or in a well-ventilated area. Avoid breathing vapor. Wash hands thoroughly after handling.
Response	: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing. If skin irritation occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.
Storage	: Store locked up. Store in a well-ventilated place. Keep cool.
Date of issue/Date of revision	: 4/2/2015. Date of previous issue : No previous validation. Version : 1 1/12

## Section 2. Hazards identification

Disposal

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

# Hazards not otherwise classified

## Section 3. Composition/information on ingredients

: None known.

Substance/mixture	1	Mixture
Other means of	:	Not available.
identification		

#### **CAS number/other identifiers**

CAS number	: Not applicable.		
Product code	: 693		
Ingredient name		%	CAS number
Distillates (petroleum), hydrotreated light Polyurethane		≥50 - <75 ≥25 - <50	64742-47-8 proprietary

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

where a laff a stall a suite and all laws a

## Section 4. First aid measures

<b>Description of necess</b>	ary first aid measures
Eye contact	<ul> <li>Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.</li> </ul>
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Date of issue/Date of revision	: 4/2/2	2015. Date of previous issue	: No previous validation.	Version : 1	2/12
Skin contact	: Cause	es skin irritation.			
Inhalation	: Can c dizzin	ause central nervous system ess.	(CNS) depression. May c	ause drowsiness an	d
Eye contact	: Cause	es serious eye irritation.			
Potential acute health effe	<u>ects</u>				
Most Important symptoms	errects, ac	ute and delayed			

# Section 4. First aid measures

Ingestion	: Can cause central nervous system (CNS) depression.
Over-exposure signs/sym	<u>ptoms</u>
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: Adverse symptoms may include the following: nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.
Indication of immediate me	dical attention and special treatment needed, if necessary
Notes to physician	<ul> <li>Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.</li> </ul>
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

# Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use dry chemical, CO <sub>2</sub> , water spray (fog) or foam.
Unsuitable extinguishing media	: Do not use water jet.
Specific hazards arising from the chemical	: Flammable liquid and vapor. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard.
Hazardous thermal decomposition products	: No specific data.
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

# Section 6. Accidental release measures

Personal precautions, prot	<u>ective equipmer</u>	nt and emergency proce	<u>dures</u>			
For non-emergency personnel	Evacuate s entering. D No flares, s adequate v	hall be taken involving an urrounding areas. Keep Do not touch or walk throu moking or flames in haza entilation. Wear appropri iate personal protective e	unnecessary and unprote gh spilled material. Shut ard area. Avoid breathing ate respirator when venti	cted perso off all igni vapor or	onnel fro tion soui mist. Pro	rces. ovide
Date of issue/Date of revision	: 4/2/2015.	Date of previous issue	: No previous validation.	Version	:1	3/12

# Section 6. Accidental release measures

For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non- emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	nt	ainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

#### Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	: Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

## Section 8. Exposure controls/personal protection

<u>Control parameters</u> <u>Occupational exposure limits</u>

# Section 8. Exposure controls/personal protection

Ingredient name	Exposure limits
Distillates (petroleum), hydrotreated light	ACGIH TLV (United States, 4/2014). Absorbed through skin. TWA: 200 mg/m <sup>3</sup> , (as total hydrocarbon vapor) 8 hours.

Appropriate engineering controls	: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation other engineering controls to keep worker exposure to airborne contaminants below recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.	/ any
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipmer will be necessary to reduce emissions to acceptable levels.	
Individual protection meas	es	
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing Wash contaminated clothing before reusing. Ensure that eyewash stations and safe showers are close to the workstation location.	
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unles the assessment indicates a higher degree of protection: chemical splash goggles. Recommended: splash goggles	ŝS
Skin protection		
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should worn at all times when handling chemical products if a risk assessment indicates this necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for differ glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.	is is c
Body protection	: Personal protective equipment for the body should be selected based on the task be performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear an static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.	ti-
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved to specialist before handling this product.	
Respiratory protection	: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must based on known or anticipated exposure levels, the hazards of the product and the working limits of the selected respirator. Recommended: half-face mask, organic v filter (Type A)	safe
Personal protective equipment (Pictograms)		

# Section 9. Physical and chemical properties

Appearance	
Physical state	: Liquid.
Color	: Amber.
Odor	: Hydrocarbon.
Odor threshold	: Not available.
рН	: Not applicable.
Melting point	: Not available.
Boiling point	: Not available.
Flash point	: Closed cup: 37.778°C (100°F)
Evaporation rate	: Not available.
Flammability (solid, gas)	: Not available.
Lower and upper explosive (flammable) limits	: Not available.
Vapor pressure	: Not available.
Vapor density	: Not available.
Relative density	: 0.86
Solubility	: Insoluble in the following materials: cold water and hot water.
Partition coefficient: n- octanol/water	: Not available.
Auto-ignition temperature	: Not available.
Decomposition temperature	: Not available.
Viscosity	: Not available.

# Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
Incompatible materials	: Reactive or incompatible with the following materials: oxidizing materials
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# Section 11. Toxicological information

#### Information on toxicological effects

#### Acute toxicity

Not available.

#### Irritation/Corrosion

Not available.

#### **Sensitization**

Not available.

#### **Mutagenicity**

# Section 11. Toxicological information

#### Not available.

### **Carcinogenicity**

Not available.

#### **Reproductive toxicity**

Not available.

#### **Teratogenicity**

Not available.

#### Specific target organ toxicity (single exposure)

Name		Route of exposure	Target organs
Distillates (petroleum), hydrotreated light	Category 3	Not applicable.	Narcotic effects

#### Specific target organ toxicity (repeated exposure)

Not available.

#### **Aspiration hazard**

Name	Result
Distillates (petroleum), hydrotreated light	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure	1	Routes of entry anticipated: Oral, Inhalation. Routes of entry not anticipated: Dermal.
Potential acute health effects		
Eye contact	:	Causes serious eye irritation.
Inhalation	1	Can cause central nervous system (CNS) depression. May cause drowsiness and dizziness.
Skin contact	1	Causes skin irritation.
Ingestion	1	Can cause central nervous system (CNS) depression.
Symptoms related to the phy	sic	cal, chemical and toxicological characteristics
Eye contact	:	Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	:	Adverse symptoms may include the following: nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness
Skin contact	:	Adverse symptoms may include the following: irritation redness
Ingestion	:	No specific data.
Delayed and immediate effec	ts	and also chronic effects from short and long term exposure
Short term exposure		
Potential immediate effects	;	Not available.
Potential delayed effects	:	Not available.
Long term exposure		
Potential immediate effects	:	Not available.
Date of issue/Date of revision		: 4/2/2015. Date of previous issue : No previous validation. Version : 1

7/12

# Section 11. Toxicological information

: Not available.
<u>cts</u>
: No known significant effects or critical hazards.
: No known significant effects or critical hazards.
: No known significant effects or critical hazards.
: No known significant effects or critical hazards.
: No known significant effects or critical hazards.
: No known significant effects or critical hazards.

#### Numerical measures of toxicity

Acute toxicity estimates

Not available.

## Section 12. Ecological information

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure
Distillates (petroleum), hydrotreated light	Acute LC50 2200 μg/l Fresh water	Fish - Lepomis macrochirus	4 days

#### Persistence and degradability

Not available.

#### **Bioaccumulative potential**

Not available.

#### **Mobility in soil**

Soil/water partition : Not available. coefficient (Koc)

Other adverse effects : No known significant effects or critical hazards.

# Section 13. Disposal considerations

Disposal methods	: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact
	cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

# Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	ADR/RID	IMDG	ΙΑΤΑ
UN number	1263	1263	1263	1263	1263	1263
UN proper shipping name	Not Regulated For Ground Transportation.	Not Regulated For Ground Transportation.	Not Regulated For Ground Transportation.	Paint	Paint	Paint
Transport hazard class(es)	3 remaining again	3	3	3 () () () () () () () () () () () () ()	3 ••••••••••••••••••••••••••••••••••••	3
Packing group	ш	Ш	Ш	Ш	Ш	ш
Environmental hazards	No.	No.	No.	Yes.	Yes.	No.
Additional information	-	-	-	The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg. <u>Special</u> <u>provisions</u> 640 (E) <u>Tunnel code</u> (D/E)	The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.	The environmentally hazardous substance mark may appear if required by other transportation regulations.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not available. to Annex II of MARPOL 73/78 and the IBC Code

**Pollutants (HAPs)** 

## Section 15. Regulatory information

U.S. Federal regulations		TSCA 8(a) CDR Exempt/Partial exemption: Not determined
		Not determined.
		Clean Water Act (CWA) 307: benzene; toluene; ethylbenzene
		Clean Water Act (CWA) 311: benzene; toluene; ethylbenzene
Clean Air Act Section 112 (b) Hazardous Air	:	Not listed

 Date of issue/Date of revision
 : 4/2/2015.
 Date of previous issue
 : No previous validation.
 Version
 : 1

9/12

# Section 15. Regulatory information

Clean Air Act Section 602 Class I Substances	: Not listed
Clean Air Act Section 602 Class II Substances	: Not listed
DEA List I Chemicals (Precursor Chemicals)	: Not listed
DEA List II Chemicals (Essential Chemicals)	: Not listed
SARA 302/304	
Composition/information	<u>on ingredients</u>
No products were found.	
SARA 304 RQ	: Not applicable.

-			
<b>SARA</b>	311/3	<u>12</u>	

**Classification** 

: Fire hazard

Immediate (acute) health hazard

#### **Composition/information on ingredients**

Name	%	Fire hazard	Sudden release of pressure	Reactive	Immediate (acute) health hazard	Delayed (chronic) health hazard
Distillates (petroleum), hydrotreated light Polyurethane	≥50 - <75 ≥25 - <50	No. No.	No. No.	No. No.	Yes. Yes.	No. No.

#### **State regulations**

Massachusetts	:	None of the components are listed.
New York	;	None of the components are listed.

New Jersey

None of the components are listed.None of the components are listed.

Pennsylvania

California Prop. 65

**WARNING:** This product contains less than 0.1% of a chemical known to the State of California to cause cancer. **WARNING:** This product contains less than 1% of a chemical known to the State of California to cause birth defects or other reproductive harm.

Ingredient name	Cancer	Reproductive	No significant risk level	Maximum acceptable dosage level
benzene	Yes.	Yes.	6.4 μg/day (ingestion) 13 μg/day	24 μg/day (ingestion) 49 μg/day
			(inhalation)	(inhalation)
toluene	No.	Yes.	No.	7000 μg/day (ingestion)
ethylbenzene	Yes.	No.	41 μg/day (ingestion) 54 μg/day (inhalation)	No.
cumene	Yes.	No.	No.	No.

#### **International regulations**

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

#### Montreal Protocol (Annexes A, B, C, E)

Not listed.

Stockholm Convention on Persistent Organic Pollutants

## Section 15. Regulatory information

Not listed.

#### Rotterdam Convention on Prior Inform Consent (PIC) Not listed.

#### **UNECE Aarhus Protocol on POPs and Heavy Metals**

Not listed.

#### International lists

National inventory	
Australia	: Not determined.
Canada	: Not determined.
China	: Not determined.
Europe	: Not determined.
Japan	: Not determined.
Malaysia	: Not determined.
New Zealand	: Not determined.
Philippines	: Not determined.
Republic of Korea	: Not determined.
Taiwan	: Not determined.

## Section 16. Other information

#### Hazardous Material Information System (U.S.A.)



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on SDSs under 29 CFR 1910. 1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

Procedure used to derive the classification

#### Marathane

## Section 16. Other information

Section 16. Other information			
Classification		Justification	
Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H336		On basis of test data Calculation method Calculation method Calculation method	
<u>History</u>			
Date of printing	: 4/2/2015.		
Date of issue/Date of revision	: 4/2/2015.	4/2/2015.	
Date of previous issue	: No previous validation.	No previous validation.	
Version	: 1		
Key to abbreviations	BCF = Bioconcentration GHS = Globally Harmoni IATA = International Air T IBC = International Air IMDG = International Ma LogPow = logarithm of th MARPOL 73/78 = International	ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)	
References	: Not available.	Not available.	

**V** Indicates information that has changed from previously issued version.

#### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.